

SPECIALTY COATINGS

Berger Commercial Grade Autospeed Primer Surfacer



PRODUCT DESCRIPTION

Berger Commercial Grade Autospeed Primer Surfacer Grey is a solvent based primer ready to be used on steel, or as a filler coat on properly prepared primed surfaces on both interior and exterior.

DESIGNED USE

- Has excellent adhesion to properly prepared surfaces
- Fast Drying
- Easy to sand
- Easy to apply and goes on flat

PHYSICAL DATA

COLOUR Grey

GLOSS Flat

FLASHPOINT 36°C

PRACTICAL COVERAGE: 6.6-7.4 m²/ liter (262.7-294.7 sq ft per 3.7L) Practical coverage depends on the porosity and texture of the surface. Some colors may require a colored primer

DRY TIME: Touch 10 mins Hard 1 hr. and Recoat 1 hr.

APPLICATION DETAILS

APPLICATION METHOD:

Spray one wet coat for the priming coat. Leave 5-10 minutes before applying filler coats. Allow 5-10 minutes between coats. Apply 2-3 normal coats. Do not build thick heavy coats.

Pack Size 1 Gallon (3.7L) and 5 Gallon (18.9L)

Thinner: Berger Reducer No.4

NO. OF COMPONENTS: 1

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely.

SPECIALTY COATINGS

Berger Commercial Grade Autospeed Primer Surfacer



SURFACE PREPARATION

NEW SURFACES

The degree of surface preparation is directly related to the performance of the coating. The surface must be dry, clean and free from all contaminants including rust and oil before coating. Treat bare metal, aluminum, zinc, copper and galvanized sheeting with Berger Etch Primer. Topcoat using Berger Commercial Grade Autospeed Primer Surfacer Grey.

PREVIOUSLY PAINTED

- Remove all rust and any loose flaking paint by abrasive blasting to expose a clean surface.
- Treat as new substrate. Rinse, dry and re-clean prior to application of Berger Commercial Grade Autospeed Primer Surfacer Grey.

SAFETY PRECAUTIONS

- Read directions carefully before using
- Keep out the reach of children
- Do not take internally • Liquid paint and vapours may cause irritation
- Use only with adequate ventilation
- To ensure the entry of fresh air, open all windows and doors
- If headache or dizziness is experienced, use respiratory protection or leave area for fresh air
- Avoid contact with skin or eyes

FIRST AID

Ingestion: Do not induce vomiting. Get medical attention immediately
Inhalation: If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
Eye Contact: Flush immediately with water for at least 15 minutes.
Skin Contact: Wash thoroughly with soap and water.

DISCLAIMER

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.

For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department.
Jan. 2025 Version 3