FURNITURE FINISHES

Berger Marine Spar Varnish



PRODUCT DESCRIPTION

Berger Marine Spar Varnish is an alkyd modified, chlorinated rubber-based varnish, specially formulated to enhance the natural beauty of wooden surfaces, with a finish that performs in even the harshest conditions. This coating is a tough, flexible, long-lasting, easy to apply varnish that protects against UV rays, sea spray and mildew, and can easily be re-applied over existing varnish in reasonably good condition. This varnish gives a traditional high-gloss finish to the interior and exterior vessels trading in coastal and tropical waters.

APPLICATION

Brush or Spray

PHYSICAL DATA

FLASH POINT 36.7 °C

COVERAGE 9.0-9.5 sq. m. / I; 358-379 sq. feet/gallon

DRYING TIME To touch in 2 hours, to recoat in 12 hours, hard dry in 24 hours

THINNER Berger No. 4 Reducer

STORAGE Store in a cool, shaded, dry area **PACK SIZE** 1 Gallon (3.7L) and 1 Quart (0.9L)

SAFETY PRECAUTIONS

READ DIRECTIONS CAREFULLY BEFORE USE

- Avoid eye contact
- Avoid contact with open lesions and wounds

FURNITURE FINISHES

Berger Marine Spar Varnish



FIRST AID

- Eyes: In the event of accidental splashes, flush eyes with water immediately and obtain medical advice
- · Skin: Wash skin thoroughly with soap and water or approved industrial cleaner
- · DO NOT USE solvent or thinners
- · Inhalation: Remove to fresh air, loosen collar and keep patient rested
- Ingestion: In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention

DISCLAIMER

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.

For specific recommendations, contact your Berger Technical Service Representative or Technical Service Department. Jan. 2025 Version 3