

BERGER



FOR LASTING BEAUTY AND PROTECTION

SAFETY DATA SHEETS



ALD PRIMER

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

IDENTIFICATION OF THE SUBSTANCE OR MIXTURE

Product name:	ALD PRIMER
Product code:	TR-1074W100
Chemical name:	Not available
Synonyms:	Not available
Chemical formula:	Not applicable
CAS number:	Not applicable

COMPANY/UNDERTAKING IDENTIFICATION

Manufacturer/Supplier: ANSA MCAL INDUSTRIAL PARK,
51-59 TUMPUNA ROAD SOUTH, GUANAPO,
ARIMA, TRINIDAD, W.I.
TEL (868) 665-5721-3/4913/5829/8046/1991, 671-2722/ 3245
FAX (868) 665-1577

Emergency telephone number
(with hours of operation): TRINIDAD
TEL : 868) 665-5721-3/4913/5829/8046/1991, 671-2722/3245
FAX: (868) 665-1577

PRODUCT INFORMATION

www.bergerpaintscaribbean.com

2. HAZARDS IDENTIFICATION

Classification:	Irritant
Risk phrases:	R43- May cause sensitization by skin contact. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Human health hazards:	May cause sensitization by skin contact.
Environmental health hazard:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Additional hazards:	None known.

See Section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation:	Mixture	
Ingredient name	CAS number	%
n-butyl acrylate	141-32-2	5 - 15
titanium dioxide	13463-67-7	5 - 15
titanium dioxide	13463-67-7	1 - 5
ammonia, anhydrous	7664-41-7	0 - 1
diuron (ISO)	330-54-1	0 - 1
carbendazim (ISO)	10605-21-7	0 - 1
octhilinone (ISO)	26530-20-1	0 - 1
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	0 - 1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.
Occupational exposure limits, if available, are listed in Section 8.

ALD PRIMER

4. FIRST AID MEASURES

INHALATION

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

INGESTION

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SKIN CONTACT

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

EYE CONTACT

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

See Section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Suitable:

Not suitable:

Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Do not use water jet.

SPECIAL EXPOSURE HAZARDS

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS

Decomposition products may include the following materials: carbon dioxide, carbon monoxide, metal oxide/oxides

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

ALD PRIMER

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

ENVIRONMENTAL PRECAUTIONS

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

METHODS FOR CLEANING UP

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

7. HANDLING AND STORAGE

HANDLING

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

STORAGE

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

ALD PRIMER

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

INGREDIENT NAME	OCCUPATIONAL EXPOSURE LIMITS
N-BUTYL ACRYLATE	<p>EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 2 ppm 8 hours. TWA: 11 mg/m³ 8 hours. STEL: 10 ppm 15 minutes. STEL: 53 mg/m³ 15 minutes.</p>
TITANIUM DIOXIDE	<p>ACGIH TLV (United States, 3/2012). TWA: 10 mg/m³ 8 hours.</p>
AMMONIA, ANHYDROUS	<p>EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 14 mg/m³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 36 mg/m³ 15 minutes.</p>
DIURON (ISO)	<p>ACGIH TLV (United States, 3/2012). TWA: 10 mg/m³ 8 hours.</p>
LIMESTONE	<p>OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust NIOSH REL (United States, 1/2013). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 6/2010). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust</p>
N-BUTYL ACRYLATE	<p>OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm 8 hours. TWA: 55 mg/m³ 8 hours. NIOSH REL (United States, 1/2013). TWA: 10 ppm 10 hours. TWA: 55 mg/m³ 10 hours. ACGIH TLV (United States, 3/2012). Skin sensitizer. TWA: 2 ppm 8 hours.</p>
TALC , CONTAINING ASBESTIFORM FIBRES	<p>OSHA PEL 1989 (United States, 3/1989). TWA: 2 mg/m³ 8 hours. Form: Respirable dust NIOSH REL (United States, 1/2013). TWA: 2 mg/m³ 10 hours. Form: Respirable fraction OSHA PEL Z3 (United States, 9/2005). TWA: 20 mppcf 8 hours. Form: not containing asbestos STEL: 1 f/cc 30 minutes. Form: not containing asbestos TWA: 0.1 f/cc 8 hours. STEL: 1 f/cc 30 minutes.</p>
TITANIUM DIOXIDE	<p>ACGIH TLV (United States, 3/2012). TWA: 10 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m³ 8 hours. Form: Total dust OSHA PEL (United States, 6/2010). TWA: 15 mg/m³ 8 hours. Form: Total dust</p>

ALD PRIMER

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RECOMMENDED PROCEDURE

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

OCCUPATIONAL EXPOSURE CONTROLS

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

HYGIENE MEASURES

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

RESPIRATORY PROTECTION

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

HAND PROTECTION

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

EYE PROTECTION

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

SKIN PROTECTION

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

ENVIRONMENTAL EXPOSURE CONTROLS

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

ALD PRIMER

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid.
ODOR	Not available.
ODOR THRESHOLD	Not available.
PH	Not available.
BOILING POINT	Not available.
MELTING POINT	Not available.
FLASH POINT	Closed cup: >61°C (>141.8°F)
VAPOR PRESSURE	Not available.
SOLUBILITY	Not available.
VAPOR DENSITY	Not available.
AUTO-IGNITION TEMPERATURE	Not available.
DENSITY	1.4218 g/cm ³
FLAMMABILITY	Not available

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY	The product is stable.
POSSIBILITY OF REACTIONS	Under normal conditions of storage and use, hazardous reactions will not occur.
CONDITIONS TO AVOID	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
MATERIALS TO AVOID	No known incompatibility

ALD PRIMER

11. TOXICOLOGICAL INFORMATION

POTENTIAL ACUTE HEALTH EFFECTS

Inhalation:	No known significant effects or critical hazards..
Ingestion:	No known significant effects or critical hazards.
Skin contact:	May cause skin irritation. May cause sensitization by skin contact..
Eye contact:	May cause eye irritation.

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
n-butyl acrylate	Eyes - Mild irritant Eyes - Mild irritant Skin - Mild irritant Skin - Mild irritant	Rabbit Rabbit Rabbit Rabbit	- - - -	24 hours 500 milligrams 50 milligrams 24 hours 10 milligrams 24 hours 500 milligrams	- - - -
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 micrograms Intermittent	-
octhilinone (ISO)	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
reaction product: 5-chloro-2-methyl-4-isothiazolin-3-one ([EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Skin - Severe irritant	Human	-	0.01 percent	-

PRODUCT NAME	CARCINOGENIC EFFECTS	MUTAGENIC EFFECTS	DEVELOPMENTAL EFFECTS	FERTILITY EFFECTS
diuron (ISO)	Carc. Cat. 3; R40			
carbendazim (ISO)		Muta. Cat. 2; R46	Repr. Cat. 2; R61	Repr. Cat. 2; R60

CHRONIC EFFECTS	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
CARCINOGENICITY	No known significant effects or critical hazards
MUTAGENICITY	No known significant effects or critical hazards
TERATOGENICITY	No known significant effects or critical hazards
DEVELOPMENTAL EFFECTS	No known significant effects or critical hazards
FERTILITY EFFECTS	No known significant effects or critical hazards
DENMARK CARCINOGEN LIST	Contains a substance or substances listed under National Working Environment Authorities Executive Order 908/2005.

OVER-EXPOSURE SIGNS/SYMPOMTS

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation, redness
Eyes	: No specific data.

ALD PRIMER

12. ECOLOGICAL INFORMATION

ECOTOXICITY	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
AQUATIC ECOTOXICITY	Conclusion/Summary: Not available.

BIOACCUMULATIVE POTENTIAL

PRODUCT/ INGREDIENT NAME	LOGP_{ow}	BCF	POTENTIAL
n-butyl acrylate	2.36	17.27	low
titanium dioxide	-	352	high
titanium dioxide	-	352	high
diuron (ISO)	2.68	14.125375446	low
carbendazim (ISO)	1.52	2.51	low
octhilinone (ISO)	2.45	-	low

OTHER ADVERSE EFFECTS	No known significant effects or critical hazards.
------------------------------	---

13. DISPOSAL CONSIDERATIONS

METHODS OF DISPOSAL	The generation of waste should be avoided or minimized wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
----------------------------	---

14. TRANSPORT INFORMATION

INTERNATIONAL TRANSPORT REGULATIONS

This preparation is not classified as dangerous according to international transport regulations (ADR/RID, ADNR, IMDG and IATA). Transport in accordance with ADR/RID, ADNR, IMDG and IATA and national regulation.

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

ALD PRIMER

15. REGULATORY INFORMATION

HAZARD SYMBOL
OR SYMBOLS:

Irritant

RISK PHRASES

R43- May cause sensitization by skin contact.
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S2- Keep out of the reach of children.
S24- Avoid contact with skin.
S37- Wear suitable gloves.
S46- If swallowed, seek medical advice immediately and show this container or label.


CONTAINS

n-butyl acrylate
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

PRODUCT USE

Consumer applications

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION
ASSOCIATION (U.S.A.)

HISTORY

Date of printing	6-12-2015.
Date of issue	1-12-2021
Revision	1
Date of previous issue	No previous validation
Version	2

Indicates information that has changed from previously issued version.

DISCLAIMER

Information contained in this material safety data sheet is believed to be reliable and given in good faith, but no representation, guarantee or warranties of any kind are made as to its accuracy, suitability for a particular application or results to be obtained from them. The user of this material decides what safety measures are necessary to safely use this material, either alone or in combination with other materials.

BERGER



FOR LASTING BEAUTY AND PROTECTION

SAFETY DATA SHEETS

This is an evolving document and will be updated periodically as new products become available.
For further support, please contact our corporate office:

ANSA Coatings Limited (Head Office)
Address: ANSA McAL Industrial Park,
#51-59 Tumpuna Road, Guanapo,
Arima, Trinidad.

