



BERGER

BRUSHING SOLUTION

Product Description

BERGER BRUSHING SOLUTION is a premium quality wall paint with a smooth, flat finish, specially formulated for Textured surfaces in a tropical climate. BERGER Brushing Solution is a low odour, low VOC, pure acrylic emulsion, with excellent durability, fungal and alkali resistance. BERGER Brushing Solution will give years of beauty and protection on exterior and interior surfaces.

Design Use

Areas of Use: Interior and Exterior
 Substrate: Overcoating textured surfaces

Physical Data

Finishes: Smooth
 Colour: Coral Stone, Natural and the Colour Library
 Spread Rate: 10.5m²/L (White) and up to 14.0 m²/L for colours. Practical coverage depends on the porosity and texture of the surface. Some colours may require a primer. Refer to the Colour Library fandeck for more information.
 Drying Time: Touch: 15 minutes; Re-coat: 1 hour.
 Gloss Levels: Flat

Application Data

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Use up to 250 mls clean water per 3.8L, for thinning if necessary for ease of application.

Brush or Roller: Apply an even coat taking care to avoid runs and sags.
 Spray: Use conventional spray equipment.

Additional Information

Thinner: Clean water
 Storage Instructions: Store in a cool, shaded, dry area
 Hazard Rating: Non-flammable; non-toxic and lead-free
 Shelf Life: 2 Years
 Pack Size: 3.785L, 18.92L

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation. BERGER Brushing Solution can also be used to beautify and protect other surfaces as follows:

CONCRETE, PLASTER, MASONRY

New Surfaces

Smooth new surfaces, removing any loose sand, mortar splashes manually or mechanically. Prime new surfaces with one coat of BERGER Alkali Sealer or BERGER Luxatex Salt Inhibitive primer after it has been allowed to weather for a minimum of 30 days. BERGER Concrete Primer may also be used as an alternative primer on new concrete surfaces, which have been weathered at least 45 days.

BERGER
 FOR LASTING BEAUTY AND PROTECTION

www.bergerpaintscaribbean.com | facebook.com/BergerCaribbean
 instagram.com/bergerpaintscaribbean

MORE OVERLEAF

Previously Painted Surfaces

Ensure surface is clean, dry and free from dust, grease, algae, dirt and all other contaminants. Treat fungal growth, by scrubbing or power washing with a 10% bleach solution. Rinse thoroughly and allow to dry. Apply one coat of BERGER Biocidal or Sterilizing Solution ensuring that there is adequate daylight remaining for drying. Do not apply if the weather is rainy.

Surfaces showing cracking, peeling, chalking or efflorescence should be wire brushed, scraped and sanded to remove loose flaking material, and reduce previous film to a flat finish. Thoroughly dust down the entire surface; then apply one coat of BERGER Alkali Sealer.

WOOD

New Surfaces

Sand new surfaces to a smooth finish. Prime lightly coloured wood with BERGER Wood Primer or BERGER Grip & Seal and dark wood with BERGER Alkali Sealer. Allow recommended time for drying.

Previously Painted Surfaces

Ensure that dirt, stains, loose material and contaminants, etc. are removed. If the surface is cracking or peeling, remove the loose material by scraping. Thoroughly dust to ensure a clean surface. Treat any fungal growth with BERGER Sterilizing Solution.

GYPSUM

Sand to a smooth finish and remove all dust. Apply one coat of Berger Alkali Sealer or Berger Luxatex Primer to seal surface, allowing recommended time for drying.

METAL SURFACES

IRON AND STEEL – should be thoroughly cleaned to remove all oil, grease, rust, scale, moisture. Prime with BERGER Metal Primer or RustPro Primer (Red/Yellow Oxide)

ALUMINIUM & ZINC – should be degreased and etched with BERGER Self Etch Primer
Contact BERGER Technical Service Department for other specific recommendations.

Health and Safety Instructions

READ INSTRUCTIONS CAREFULLY BEFORE USE.

Do not take internally. Liquid paint and vapours may cause irritation. Use only with adequate ventilation. To ensure the entry of fresh air, open all windows and doors. If headache or dizziness is experienced use respiratory protection or leave area for fresh air. Avoid contact with skin and eyes.

HEALTH & SAFETY: Water based.

First Aid

Ingestion:	Do not induce vomiting. Get medical attention immediately.
Inhalation:	If excessive exposure symptoms are experienced, leave area to obtain fresh air. If difficulty continues, seek immediate medical attention.
Eye Contact:	Flush immediately with water for at least 15 minutes.
Skin Contact:	Wash thoroughly with soap and water.

Contact Us



BERGER Paints Barbados Ltd.

Exmouth Gap, Brandons, St. Michael,
Bridgetown, Barbados, W.I. BB12069

Tel: +1-246-425-9073

Fax: +1-246-228-0866

Email: info@bergercaribbean.com

www.bergerpaintscaribbean.com | [facebook.com/BergerCaribbean](https://www.facebook.com/BergerCaribbean) | [instagram.com/bergerpaintscaribbean](https://www.instagram.com/bergerpaintscaribbean)

These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patent or regulations. For specific recommendations, contact your BERGER Technical Service Representative or Technical Service Department.

